


P2-WS102-0868-R

Single Input Wireless Transmitter Roaming



For use with the D3 868Mhz family of wireless base stations
Compatible with a range of P3-DS Intelligent Digital Sensors (supplied separately)

Product Drawing:



Designed to work with tek troniks D3 868Mhz wireless base stations and is compatible with a range of tek troniks Intelligent sensors.

Secure communication protocols using licence free 866Mhz radio frequency.

Bi directional wireless communications with the base station allows for communication status reporting.

1 to 30 minute record intervals allowing for up to 30 days of data storage.

Automatically downloads stored data when within communications distance of the D3 868Mhz wireless network.

Technical Specifications:

Transmission Frequency: _____	1 minute	Status LED: _____	Provides communication status
RF Frequency: _____	868 Mhz	Weight: _____	77g
	14dbm - UK & Europe	IP Rating: _____	IP67
RF Range: _____	1 kilometre (line of sight, open field)	Connector: _____	2 x 3 pin female Hirose
	200m typical in buildings	Operating Temperature: _____	-20°C to 55°C
	Extenders available to boost range	Battery Life: _____	>2 years based on daily return
Data Storage: _____	1 day at 1 minute Interval	Battery Type: _____	3.6V lithium
	up to 30 days at 30 minute Intervals	Mounting: _____	Integral magnetic strip or optional mounting bracket



Doc: 106-10065-01 (Datasheet - P2-WS102-0868-R)

Visit: www.tek-troniks.com Call: 0115 9890090

Product Disclaimer:

The recommendations and suggestions regarding product application and use that are offered on Tek-troniks.com, in our product brochures, datasheets, or information provided by any employee or distributor, are a guide in the use of this product and are not a guarantee to their performance. Tektroniks reserve the right to alter specification of their products without prior warning or notification. Always read instruction manuals fully before installing any Tektroniks component.