


P3-DS300-RJ

NTC Air Sensor Open/Internal Mount

For use with the D3 family of wireless base stations
Compatible with a full range of Intelligent Wireless Transmitters (supplied separately)

Product Drawing:



The probe utilises a NTC thermistor which offers excellent stability and low drift over the lifetime of the sensor.

Designed to be used as an internal sensor or external air sensor.

Common uses:
Fridges | Cold Rooms | Production Areas

This product can be supplied with a calibration certificate.

Technical Specifications:

Temperature Range: _____ -20°C to 45°C
Accuracy: _____ Standard - $\pm 0.5^\circ\text{C}$ over range
Calibrated - $\pm 0.2^\circ\text{C}$ over range
Thermistor: _____ NTC 5K R/T curve 8016/A01
Weight: _____ 6g

Connector: _____ RJ11
Operating Temperature: _____ -20°C to 45°C
Sensor Sheathing: _____ Technomelt OM678

Compatible Tek Troniks full range of P2-WS2xxx Wireless Transmitters



Doc: 106-10169-01 (Datasheet - P3-DS300-RJ)

Visit: www.tek-troniks.com Call: 0115 9890090

Product Disclaimer:

The recommendations and suggestions regarding product application and use that are offered on Tek-troniks.com, in our product brochures, datasheets, or information provided by any employee or distributor, are a guide in the use of this product and are not a guarantee to their performance. Tektroniks reserve the right to alter specification of their products without prior warning or notification. Always read instruction manuals fully before installing any Tektroniks component.